

INDIAN INSTITUTE OF TECHNOLOGY PALAKKAD

Name of work:Supply of Classroom chair -Single seater (Flap chair)in Transit campus IIT Palakkaad

The following corrigendum in respect of above work is issued

Corrigendum No.2 Dated:23-04-2018

Ref:Tender no. IITPKD/ADMN/02/2018 Date:18/04/2018

Ref to para	As per tender	May be read as
1 st Para	Type of seat and backrest:- 19 mm thick hot compressed boiled water resistant plywood glued with PU coated high quality veneers	Type of seat and backrest:- 19 mm thick moulded compressed boiled water resistant plywood glued with PU coated high quality veneers
1.a)	For seat and leg:-32 mm x32 mm, wall thickness 2 mm thick CRCA hollow tube	For seat and leg:-30 mm x30 mm, wall thickness 1.6 mm thick CRCA hollow tube
1.b)	Base for leg-550 mm long x 32x 32x 2 mm thick CRCA hollow tube	Base for leg-550 mm long x 30x 30x 1.6 mm thick CRCA hollow tube
10)	Colour of seat and backrest :- Cherry red	Colour of seat and backrest :- Bavarian Beech
		Side view of leg frame photo added
		Front view photo added
		Writing pad photo added

Registrar, IIT Palakkad



NOTE:

19 mm thick moulded compressed boiled water resistant plywood

WRITING PAD



SIDE VIEW OF LEG FRAME

Base Frame for leg :

**550 mm long , 30 x 30 x 1.6 mm
thick CRCA hollow tube
including necessary neo prene
bushes**



Back Rest : 425 mm wide (465 mm curved length) x 380 mm height

Frame for Back rest : 2 Nos 38 x 15 x 1.6 mm thick CRCA Elliptical hollow section

Seat : 440 mm wide (460 curved length) X 400 mm Depth

Writing Pad : 550 mm X 250 mm & Minimum width 85 mm

Under Storage Unit made up of 6 mm dia MS rod
4 Nos Horizontal & 11 Nos Vertical MS rod
suspended from seat frame by 4 Nos 20x20x2.9 mm
(280 mm long from seat frame)

Leg frame : 30 x30 x1.6 mm thick CRCA hollow section